

GENERAL NOTES:

1. SYSTEM SHOULD ONLY BE USED ON FLAT SURFACES NOT TO EXCEED $\frac{1}{2}$ " : 12" PITCH.
2. END ALL CONFIGURATIONS WITH EITHER A CLOSED LOOP THAT CONNECTS ALL BASES AND RAIL SECTIONS OR A 90° 5' OUTRIGGER SYSTEM TO PROVIDE NEEDED COUNTERBALANCE.
3. SMOOTH SURFACES SUCH AS METAL OR CONCRETE MUST UTILIZE RUBBER PADS ON THE BOTTOM OF THE BASE PLATE.
4. REMOVE ALL LOOSE GRAVEL AND/OR MATERIALS IN THE VICINITY OF RAILING SYSTEM. BASES MUST BE PLACED ON SOUND SUBSTRATE.
5. RAILINGS MUST BE CONNECTED TO THE STEEL BASE PLATE WITH PINS AT ALL TIMES.
6. TOEBOARDS SHOULD BE USED WHEN THERE IS DANGER OF MATERIALS BEING KICKED OR FALLING TO THE LEVEL BELOW.
7. SYSTEM IS DESIGNED TO BE USED AT THE LEADING EDGE WITH NO SPECIFIED SETBACK REQUIREMENT.

DESIGN NOTES:


1. DESIGNED TO COMPLY WITH OSHA CFR 1910.23 AND 1926.500-503.
2. SYSTEM IS DESIGNED TO WITHSTAND A 200 lb. CONCENTRATED LOAD LOCATED AT ANY POINT ALONG THE TOP RAILING.
3. TOP EDGE HEIGHT OF THE TOP RAIL IS TO BE INSTALLED BETWEEN 39 AND 45 INCHES ABOVE THE WALKING/WORKING LEVEL.

Warning: Failure to comply with manufacturer's installation procedures may result in property damage, personal injury or death. Only qualified persons experienced in these installation methods shall install Peak Fall Protection's equipment. If method of installation is not understood do not attempt to install this equipment.

Series Name: Ballasted Roof Mount Guardrail
Series Number: BRM-GR 4000

Rated Load: 200 lbs Concentrated Load

THESE DRAWINGS ARE THE PROPERTY OF PEAK FALL PROTECTION INC., 1230 PERRY RD. APEX N.C. 27502, AND SHALL NOT BE USED, COPIED, OR REPRODUCED WITHOUT WRITTEN PERMISSION.



PEAK FALL PROTECTION

DESIGNED SAFETY SOLUTIONS

1230 PERRY RD. APEX, NC 27502

PH 866-387-9965 FAX 919-387-9914

WWW.PEAK-FP.COM