



**GENERAL NOTES:**

1. SYSTEM SHOULD ONLY BE USED ON FLAT SURFACES NOT TO EXCEED  $\frac{1}{2}$ " : 12" PITCH.
2. END ALL CONFIGURATIONS WITH EITHER A CLOSED LOOP THAT CONNECTS ALL BASES AND RAIL SECTIONS OR A 90° 6' OUTRIGGER SYSTEM TO PROVIDED NEEDED COUNTERBALANCE.
3. SMOOTH SURFACES SUCH AS METAL OR CONCRETE MUST UTILIZE RUBBER PADS ON THE BOTTOM OF THE BASE. DO NOT INSTALL ON SLIPPERY SURFACES SUCH AS METAL OR TROWEL FINISHED CONCRETE.
4. REMOVE ALL LOOSE GRAVEL AND/OR MATERIALS IN THE VICINITY OF THE RAILING SYSTEM. BASES MUST BE PLACED ON SOUND SUBSTRATE.
5. RAILINGS MUST BE CONNECTED TO THE STEEL BASE WITH SET SCREWS AT ALL TIMES.
6. TOEBOARDS SHOULD BE USED WHEN THERE IS DANGER OF MATERIALS BEING KICKED OR FALLING TO THE LEVEL BELOW.
7. WHEN PARAPET DOES NOT EXIST, FRONT EDGE OF BASE SHALL BE SET BACK A MINIMUM OF 24" FROM THE LEADING EDGE.

**DESIGN NOTES:**

1. DESIGNED TO COMPLY WITH OSHA CFR 1910.23 AND 1926.500-503.
2. SYSTEM IS DESIGNED TO WITHSTAND A 200 LB CONCENTRATED LOAD AT ANY POINT ALONG THE TOP RAILING.
3. TOP EDGE HEIGHT OF THE TOP RAIL IS TO BE INSTALLED BETWEEN 39 AND 45 INCHES ABOVE THE WALKING/WORKING LEVEL.

**WARNING:** FAILURE TO COMPLY WITH MANUFACTURER'S INSTALLATION PROCEDURES MAY RESULT IN PROPERTY DAMAGE, PERSONAL INJURY OR DEATH. ONLY QUALIFIED PERSONS EXPERIENCED IN THESE INSTALLATION METHODS SHALL INSTALL PEAK FALL PROTECTION'S EQUIPMENT. IF METHOD OF INSTALLATION IS NOT UNDERSTOOD, DO NOT ATTEMPT TO INSTALL THIS EQUIPMENT.

SERIES NAME: LORGUARD GUARDRAIL  
 SERIES NUMBER: PGR-7900  
 RATED LOAD: 200 LBS CONCENTRATED LOAD

THESE DRAWINGS ARE THE PROPERTY OF PEAK FALL PROTECTION LLC, AND SHALL NOT BE USED, COPIED, OR REPRODUCED WITHOUT WRITTEN PERMISSION.



A Diversified Fall Protection Company

INFO@PEAK-FP.COM

PH 866-387-9965

WWW.PEAK-FP.COM